



## Data Sheet

# Firetherm Fire Rated Foam

### Application

**Fire Rated Foam** is designed to be used to fire stop small gaps and service penetrations in masonry walls and floors around pipes and cabling, and to bond and seal around fire door frames and windows.

### Description

Fire Rated Foam is a moisture curing foam suitable for use in gaps up to 40mm (2 hour fire integrity), around services or bonding door and window frames having excellent adhesion to most building materials.

### Specification Wording

“Install **Firetherm Intuputty** to provide fire seals for (1,2 and 4hr) fire protection fully in accordance with **Firetherm’s** Installation Instructions. **Firetherm**, Crayford, England. Tel +44 (0) 1322 551010.”

### Testing

Fire tested to BS 476 Pt 20/22 for up to 4 hours fire integrity and insulation.

### Benefits

Suitable for many applications, bonding to a wide range of substrates. Once cured the foam can be easily cut or sawn. Cures in one hour.

### Application Instructions

- 1 Read the Fire Rated Foam Health & Safety instructions before starting work.
- 2 Ensure surfaces to be treated are free from grease, dust and loose materials.
- 3 Refer to Fire Rating below for seal fire rating and construction.
- 4 Moisten surfaces to improve curing time.

- 5 Shake can for 30 seconds and occasionally during use.
- 6 Hold can upside down, work away from you on horizontal surface and bottom up on vertical surface.
- 7 Only partially fill cavity as the foam will expand to fill remaining space.
- 8 After use, turn can upright and press nozzle to clear out foam. Fresh marks can be removed by acetone, cured foam can only be removed by mechanical means.

**Fire Rating**

Seals may be up to 50mm wide and are as specified below :

**Fire Rated Foam in Walls**

Width up to (mm)	Depth of seal for Integrity and Insulation (mm)		
	60 minutes	120 minutes	240 minutes
15	120	150	220
20	140	220	N/A
25	160	N/A	N/A

**Fire Rated Foam in Floors**

Width up to (mm)	Depth of seal for Integrity and Insulation (mm)		
	60 minutes	120 minutes	240 minutes
15	120	150	N/A
20	140	150	N/A
25	160	N/A	N/A

Sound absorption

LFT 167 31008/Z2 up to 56dB

Fire Rated Foam with 110kg mineral wool insulation in floors or walls

Width up to (mm)	Depth of seal for 240 minutes integrity and insulation (mm)	Mineral Wool Depth (mm)
25	220	50
50	250	100

### **Storage**

Shelf life is 12 months.

Store upright between 10°C and 25°C.

***Firetherm Intumescent & Insulation Ltd, Unit F, Acorn Industrial Park, Crayford Road, Crayford, Kent. DA1 4FT. Tel: +44 (0)1322 551010. Fax: (0)1322 552727. Website: [www.firetherm.com](http://www.firetherm.com)***

***In presenting this technical advice we cannot claim to serve in any but an advisory capacity and can undertake no liability since actual conditions of use are beyond our control.  
Our Standard Terms & Conditions Apply At All Times***